Mounting Instructions for Metal Frames



Figure 1



Figure 2



Figure 3

Mounting Instructions for Metal Frames

1 After unwrapping, remove the H-shaped frame from the infrared panel by moving it in the direction of the arrow /Figure 1/.

2 You can find 4 pieces of fixing brackets on the edges of the H-shaped frame /Figure 2, symbol 1/.

3 You can find 4 pieces of DN5 holes on the frame /Figure 2, symbol 2/, which must be used for fixing the frame /you will need DN 8 wall plugs, and DN5 screws, with a length depending on the type of the ceiling/.

4 Out of the 4 pieces of fixing brackets, 1 piece of bracket has a narrowed section /Figure 2, symbol 5/. **You can find an explanatory label next to it** /Figure 2, symbol 3/.

5 On the back of the infrared panel /the surface with the heat reflective material/, there are 4 protruding screw heads /Figure 3/.

6 Put those protruding screw heads into the wider section of the hole in the fixing brackets /Figure 2, symbol 4/.

7 When all four screw heads have been put into the wider section of the hole in the fixing bracket, the infrared panel must be pushed in the direction of the arrow up to the stop. / WARNING: IN THIS POSITION, THE INFRARED PANEL IS NOT FASTENED. /The panel might fall down.

8 The explanatory label next to the fixing bracket with the narrowed hole section /figure 2, symbol 3/ shows the correct method of mounting.

9 The heads of the protruding screws adjusted into the holes according to section 7 of these instructions must be pushed through the narrow section of the hole by a decisive strike /with a fist or a rubber hammer//Figure 2, symbol 5/. The infrared panel is fastened stably now.